




# genuwall Hardware



Model	XSi	
<b>Hardware</b>		
Revision	2.0	
CPU	2 Cores, 1GHz	
Memory	2 GB	
Network interfaces	4 x 1 Gbit/s	
Flash	16 GB	
Serial	2	
Graphical	-	
USB	2.0	
Smartcard reader	optional extern	
<b>Performance</b>		
Firewall TCP <sup>1</sup>	940 Mbit/s	
Firewall UDP <sup>2</sup>	980 Mbit/s	
<b>Chassis</b>		
Power supply	extern, Phoenix connector	
Power consumption	max. 15 W	
BTU	max. 51.15 BTU/h	
Fixture	top hat rail clip	
Width	153 mm	
Height	50 mm	
Depth	110 mm/130 mm (with Phoenix connector)	
Weight	800 g	
<b>Environment</b>		
	<b>Operation</b>	<b>Storage</b>
Voltage	9–36 V DC, min. 0.2 A, max. 1.5 A	–
Temperature	0–60° C at 50 % humidity, non condensing	-20–70° C at 50 % humidity, non condensing
Humidity	20–80 % non condensing	10–90 % non condensing
Shock	1 G 11 ms half-sine	10 G 11 ms half-sine
Vibration	5–500 Hz, PSD 0.02 G <sup>2</sup> /Hz 0.5 Grms	5–500 Hz, PSD 0.02 G <sup>2</sup> /Hz 0.5 Grms
Norms	CE	–

<sup>1</sup> TCP packets: 1448 byte

<sup>2</sup> UDP packets: 1470 byte