

Hardware



Central Management Station



| MODEL | L | M | S |
|-----------------------------------|--|--|------------------|
| Hardware | | | |
| Revision | 3.0 | 3.0 | 3.0 |
| CPU | 8 Cores, 3.7 GHz | 6 Cores, 3.4 GHz | 4 Cores, 2.7 GHz |
| Memory | 64 GB ECC | 32 GB ECC | 16 GB ECC |
| Network interfaces min. | 4 x 1 Gbit/s | 4 x 1 Gbit/s | 4 x 1 Gbit/s |
| Network interfaces max. | 16 x 1 Gbit/s | 10 x 1 Gbit/s | 8 x 1 Gbit/s |
| Network interfaces 10 Gbit/s max. | 8 x 1 Gbit/s + 8 x 10 Gbit/s ¹ | 4 x 1 Gbit/s + 4 x 10 Gbit/s ¹ | - |
| Flash Drive | 250 GB SSD | 250 GB SSD | 250 GB SSD |
| RAID level | 1 | 1 | - |
| DVD-ROM Drive | + | + | + |
| Graphics Connector | VGA | VGA | VGA |
| Serial Ports | 2 | 2 | 2 |
| USB Port | 3.0 | 3.0 | 3.0 |
| Smartcard Slot | Format ID-1 | Format ID-1 | Format ID-1 |
| Chassis | | | |
| Power Supply | 2 x 650 W | 2 x 300 W | 250 W |
| Power consumption load | 210 W | 170 W | 60 W |
| BTU/h load | 716 | 580 | 210 |
| Fixture | 19" rackmount | 19" rackmount | 19" rackmount |
| Width | 430 mm (19") | 430 mm (19") | 430 mm (19") |
| Height | 88 mm (2 U) | 44 mm (1 U) | 44 mm (1 U) |
| Depth | 635 mm | 635 mm | 470 mm |
| Weight | 13 kg | 11 kg | 6 kg |
| Weight (incl. Packaging) | 19 kg | 17 kg | 12 kg |

¹1/10 Gbit/s SFP+, multi- or mono-mode fiber optic transceiver optional

Hardware



| L | ENVIRONMENT OPERATION | ENVIRONMENT STORAGE |
|-------------|---|--------------------------|
| Voltage | 100 - 240 V AC, 60 - 50 Hz, 8 - 4 A, connector 2x IEC-C14 | - |
| Temperature | 10 - 35 °C | -20 - 70 °C |
| Humidity | 20 - 80 % non condensing | 10 - 80 % non condensing |
| Shock | 25 G / 2 ms | 300 G / 2 ms |
| Vibration | 5 - 500 Hz / 0.5 G | 0 - 500 Hz / 3 G |
| Norms | CE | - |

| M | ENVIRONMENT OPERATION | ENVIRONMENT STORAGE |
|-------------|---|--------------------------|
| Voltage | 100 - 240 V AC, 60 - 50 Hz, 5 - 3 A, connector 2x IEC-C14 | - |
| Temperature | 10 - 35 °C | -20 - 70 °C |
| Humidity | 20 - 80 % non condensing | 10 - 80 % non condensing |
| Shock | 25 G / 2 ms | 300 G / 2 ms |
| Vibration | 5 - 500 Hz / 0.5 G | 0 - 500 Hz / 3 G |
| Norms | CE | - |

| S | ENVIRONMENT OPERATION | ENVIRONMENT STORAGE |
|-------------|---|--------------------------|
| Voltage | 100 - 240 V AC, 60 - 50 Hz, 4 - 2 A, connector 1x IEC-C14 | - |
| Temperature | 10 - 35 °C | -20 - 70 °C |
| Humidity | 20 - 80 % non condensing | 10 - 80 % non condensing |
| Shock | 25 G / 2 ms | 300 G / 2 ms |
| Vibration | 5 - 500 Hz / 0.5 G | 0 - 500 Hz / 3 G |
| Norms | CE | - |