

Hardware



Hochsichere VS-NfD-konforme
Zertifikatslösung



MODEL	genuscreen XS
Hardware	
Revision	2.1
CPU	2 Cores, 1.58 GHz
Memory	4 GB
Network interfaces default	4 x 1 Gbit/s
Optional network cards	-
Available network cards	-
Flash Drive	16 GB
DVD-ROM Drive	-
Graphics Connector	-
Serial Ports	2
USB Port	2.0
Smartcard Slot	Format ID-1
Chassis	
Power Supply	40 W
Power consumption load	15 W
BTU/h load	51.15
Fixture	19" rackmount optional
Width	270 mm
Height	44 mm (1 U)
Depth	198 mm
Weight	1.8 kg
Weight (incl. Packaging)	3.0 kg

Hardware



genuscreen XS	ENVIRONMENT OPERATION	ENVIRONMENT STORAGE
Voltage	90 - 240 V AC, 60 - 50 Hz, 1 - 0.5 A, connector 1x IEC-C14	-
Temperature	0 - 50 °C at 50 % humidity, non condensing	-20 - 70 °C at 50 % humidity, non condensing
Humidity	20 - 80 % non condensing	10 - 90 % non condensing
Shock	1 G 11 ms half-sine	10 G 11 ms half-sine
Vibration	5 - 500 Hz, PSD 0.02 G ¹ /Hz, 0.5 Grms	5 - 500 Hz, PSD 0.02 G ¹ /Hz, 0.5 Grms
Norms	CE	-

¹ tcp relay, packets: TCP 1448 byte