

## Hardware



### Industrial Firewall



MODEL	XSi
<b>Hardware</b>	
Revision	3.0
CPU	Intel Celeron N2807 (2 Cores, 1.58 - 2.16 GHz)
Memory	2 GB
Network interfaces default	4 x 1 Gbit/s RJ45
Optional network cards	-
Available network cards	-
Flash Drive	1 x 32 GB SSD
DVD-ROM Drive	-
Graphics Connector	-
Serial Ports	2 x RS-232
USB Port	1 x High-Speed Type-A, 1 x USB 5Gbps Type-A
Smartcard Slot	optional extern
<b>Performance</b>	
Firewall TCP	940 Mbit/s <sup>1</sup>
Firewall UDP	1970 Mbit/s <sup>2</sup>
<b>Chassis</b>	
Power Supply	optional extern
Power consumption load	15 W
BTU/h load	50
Fixture	DIN rail mount
Width	50 mm
Height	153 mm
Depth	110 mm / 130 mm (with Phoenix connector)
Weight	0.9 kg
Weight (incl. Packaging)	1.7 kg

<sup>1</sup> tcp packets: 1448 byte

<sup>2</sup> udp packets: 1500 byte bidirectional

## Hardware



XSi	ENVIRONMENT OPERATION	ENVIRONMENT STORAGE
Voltage	24 V DC (15 - 36 V DC), min. 0.2 A, max. 1.5 A Not suitable for floating ground operation!	-
Temperature	0 - 60 °C at 50 % humidity, non condensing	-20 - 70 °C at 50 % humidity, non condensing
Humidity	20 - 80 % non condensing	10 - 90 % non condensing
Shock	1 G 11 ms half-sine	10 G 11 ms half-sine
Vibration	5 - 500 Hz, PSD 0.02 G <sup>2</sup> /Hz, 0.5 Grms	5 - 500 Hz, PSD 0.02 G <sup>2</sup> /Hz, 0.5 Grms
Norms	CE	-