



genucenter Hardware



Model	L	M	S
Hardware			
Revision	2.0	2.0	2.0
CPU	8 Cores, 3.2 GHz	4 Cores, 3.5 GHz	4 Cores, 2.4 GHz
Memory	64 GB ECC	16 GB ECC	8 GB ECC
Network interfaces min.	2 x 1 Gbit/s	4 x 1 Gbit/s	4 x 1 Gbit/s
Network interfaces max.	16 x 1 Gbit/s ^{1,2}	10 x 1 Gbit/s ^{1,2}	6 x 1 Gbit/s
Flash	250 GB SSD	250 GB SSD	250 GB SSD
RAID-level	1	1	-
DVD-RW	+	+	+
Graphical	VGA	VGA	VGA
Serial	2	2	2
USB	3.0	3.0	3.0
Chassis			
Power supply	2 x 650 W	2 x 300 W	1 x 250 W
Power consumption	max. 180 W	max. 160 W	max. 60 W
BTU	max. 613.8 BTU/h	max. 545.6 BTU/h	max. 204.6 BTU/h
Fixture	19" rackmount	19" rackmount	19" rackmount
Width	430 mm (19")	430 mm (19")	430 mm (19")
Height	88 mm (2 U)	44 mm (1 U)	44 mm (1 U)
Depth	635 mm	635 mm	470 mm
Weight	max. 19 kg	max. 17 kg	12 kg

¹ Fiber optional ² 10 Gbit/s optional

Environment	Operation	Storage
Voltage L	100–240 V AC, 50–60 Hz, 8–4 A, connector 2x IEC-C14	-
Voltage M	100–240 V AC, 50–60 Hz, 5–3 A, connector 2x IEC-C14	-
Voltage S	100–240 V AC, 50–60 Hz, 4–2 A, connector 1x IEC-C14	-
Temperature	10–35° C	-20–70° C
Humidity	20–80 % non condensing	10–80 % non condensing
Shock	25 G/2 ms	300 G/2 ms
Vibration	5–500 Hz/0.5 G	0–500 Hz/3 G
Norms	CE	-